

Selleys Liquid Nails Extreme Grab

Description

Selleys Liquid Nails Extreme Grab is a high performance construction adhesives designed for vertical applications that delivers an instant hold on most building materials*. Its high strength and resistance to heat and water make it suitable for both indoor and outdoor use**. The extreme grab formulation means you won't need fasteners or clamps^, allowing you to complete your projects quickly.

Product Information

Packaging	Size	Colour
Cartridge	290 mL	White

Uses

Liquid Nails Extreme Grab is suitable for use on materials such as timber, MDF, particleboard, masonry, concrete, metals, glass, tiles, ceramics and some plastics*.

Ideal for jobs that require high strength and grab without the need for fasteners or clamps*.

Features

- Nail-free bonding of heavy materials*
- Up to 400kg/m² instant grab^
- Remains flexible
- Interior/Exterior**
- Highly Flexible
- Strength up to 100 tonnes/m²*
- Cures in 7 days
- Paintable with water-based paints after 24 hours. Solvent-based paints may be used after first painting with a water-based paint
- UV, heat and water resistant.
- Adheres to wet/damp surfaces.
- Bridges gaps up to 9mm

Technical Details

Property	Typical Result
Appearance	Smooth white paste
Technology	Moisture cure
Service Temperature	Up to 70°C
Cure Time	7 days
Shelf Life	12 months

Indicative data only, not intended for preparation of specifications.

Application

1. Ensure surfaces are clean and free from dust, oil, grease or loose particles.
2. Use a high thrust caulking gun and the supplied V-nozzle to apply in vertical stripes 5cm apart. Ensure the V shape is angled upward when applying.
3. Position materials and press together firmly. Due to the high initial hold of the product, support during cure is not usually necessary^ (subject to weight limitation for non-porous surfaces). Use with mechanical fasteners in high stress applications.
4. Holds instantly but must not be disturbed until cured.
5. Repositionable for up to 15 minutes.

Clean Up

Clean up with turps before Instant Hold cures. Cured adhesive can be removed by scraping or sanding or with the help of Selleys silicone remover.

Notes and Limitations

- Do not use as the sole support in overhead applications
- *Not suitable for polyethylene, polypropylene, PTFE or some rubbers. Test compatibility with plastics and rubbers before use.
- ^Holds instantly but must not be disturbed until fully cured. Expect longer cure times in cold or less humid weather and for less porous surfaces. Best results are obtained where one substrate is porous. Support must be used where objects exceed 5kg or in overhead applications. Weight is restricted for non-porous substrates (e.g. metal & glass) or on hot surfaces.
- * Timber to timber bond in shear at 1mm spacing. Do not use as the sole support for structural bonding.
- **Not suitable for surfaces/areas that will exceed 70°C.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com.au

Disclaimer

All information contained in this Product Information Sheet is provide on good faith basis and is as accurate and up-to-date as possible on the date of issue. Products can be expected to perform as indicated in this Sheet, provided all application procedures are followed without exception. Notwithstanding the above, any recommendations made by Selleys or its distributors in relation to this or other products is to be taken as general

Selleys Liquid Nails Extreme Grab

advice only. Selleys makes no representations or warranties that this product will be suitable for any particular use or purpose. Subject to any applicable legislation which cannot be excluded (such as the Australian Consumer Law), Selleys accepts no responsibility and will not be held liable for any failure in performance of this product or any losses, damages, or injuries (consequential or otherwise) arising from the storage, mixing, application or other use of this product or for any representations made by third parties about the product which have not been approved in writing by Selleys. Users of this product accept all risk and responsibility for its use. Selleys recommends users undertake their own risk assessment prior to use and it is the user's sole responsibility to determine the suitability of the product for any intended use. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it provides the desired performance. For technical support please contact a Selleys representative.

This Product Information Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Selleys'). It may not be varied

or altered without the prior written consent of Selleys, and if it is, Selleys has no responsibility or liability for those variations.